

UV Wall Printer

Flagship 3-axis platform — UV LED config

The same flagship platform in its UV LED config — cures on contact for durable, exterior-facing output that comes off the wall fast.

TECHNICAL SPECIFICATIONS

Platform / motion	3-axis vertical, rail-guided carriage
Print heads	Tier-1 piezo
Ink system	UV-curable, 6-color CMYK + Lc + Lm
Curing	UV LED cure, on contact
XY resolution	720–1440 DPI
Relief / Z axis	Flat (no relief build)
Print speed*	8–12 m²/h standard* · 4–6 m²/h high-detail*
Print reach	Floor to 3.2 m · up to 15 m/session with repositioning
Best-fit surfaces	Broad substrate, incl. exterior & high-wear
Machine weight	~70 kg
Parts warranty	12-month

*Throughput is a typical range for this machine and varies with artwork complexity, resolution and surface — it is not a fixed guarantee. Figures are per this machine only; do not read across to other models.

WARRANTY & SUPPORT

12-month parts warranty · core parts stocked ≥ 5 years · 7-day transit damage cover · single unit, no full-container minimum.

CERTIFICATIONS

CE

FCC

RoHS

ISO 9001

Third-party validated (TÜV-equivalent). Certificate copies released with your quote under NDA.